



TECHNICAL DATA SHEET

SK2PP250-1 Heavy duty peel ply

► DESCRIPTION

SK2PP250-1 is a non-coated heavy duty peel ply, used for reduce or eliminate the need for sanding or abrading by producing of composite laminates. This fabric is scoured and heat set to remove contaminates and reduce shrinkage.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

		Test method
Composition:	Nylon (Polyamide)	
Colour:	White	
Wrap:	Polyamide HT 235 DTEX	NF GO1074
Weft:	Polyamide HT 235 DTEX	
Weave count (yarn/cm):	22 x 21, 5 ± 1cm	NF GO7155
Normal weight:	110g/m ²	NF GO7150
Width cm:	160 cm usable	
Weave:	Plain weave fabric	
Treatment:	heat set	
Tensile strength warp:	>150 daN	ISO 13934-1
Tensile strength weft:	>150 daN	ISO 13934-1
Elongation warp %:	25%	ISO 13934-1
Elongation weft %:	25%	ISO 13934-1
Max use temperature:	250°C	

► SIZE

Thickness	Width	Length
200µm	1600mm	100 m

Shelf life: unlimited

Storage conditions: it is recommended to store at temperatures between -20°C and +30°C in original packing.