



TECHNICAL DATA SHEET

SK2PP200-5 Tight woven peel ply

► DESCRIPTION

SK2PP200-5 is a polyester tight woven peel ply for texturing the surface of composite laminate. It is used to texture the surface of a composite laminate. The peel ply surface is helpful for secondary bonding or painting of the composite laminate. SK2PP200-5 has no coating, assist or eliminate the need for sanding or abrading on your composite laminate. The fabric is scoured and heat set to remove most contaminants and reduce shrinkage.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Material type:	Polyester
Color:	White
Surface weight:	60 g/m ² ± 10%
Recommended use temperature:	190°C
Max. use temperature*:	200°C

► SIZE

Thickness	Width	Length
50µm	1500mm	100m

Shelf life: unlimited

Storage conditions: it is recommended to store at temperature from -20°C until +30°C in original packing.

► NOTE

Peel plies are treated in order to remove all pollutant products (like silicones for example), which could be found on the laminate.

Hot knife slitting of the 1 master roll is possible upon request. 1 master roll is a minimum order quantity.

* Maximum use temperature should be determined in actual process conditions.

The maximum use temperature depends on the duration at maximum temperature and is process specific, we recommend testing prior to use.