MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

► SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Name of product: SK2TR150-1 Article: Release Paste

Company name: VIK-Composite Street/POB No.: Carl-Zeiss-Str. 11

State/city/postal code: Germany, Waldstetten 73550

Telephone: +49 7171 874 2923
Telefax: +49 7171 874 2924
E-mail: sales@vik-composite.com
Description: Solvent-based cleaner

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

STOT SE 3 H336 May cause drowsiness or dizziness.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements. Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

Signal word Warning

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

Hazard statements

H336 May cause drowsiness or dizziness

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.



MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell. P312

P405 Store locked up.

Store in a well-ventilated place. Keep container tightly closed. P403+P233

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

2.3 Other hazards Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

► SECTION 3: COMPOSITION/INFORMATION ON INGRIDIENTS

3.2 Chemical characterisation: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy > 50%

EINECS: 265-150-3 Xn R65

R66-67

Carc. Cat. 2, Muta. Cat. 2

🚸 Flam. Liq. 3, H226; 🕸 Asp. Tox. 1, H304; 🕦 STOT SE 3, H336; Aquatic Chronic

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly. After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full iet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray. Collect contaminated firefighting water separately. It must not enter the sewage system.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid contact with the eyes and skin.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

► SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves**

Nitrile rubber. BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles



Body protection: Protective work clothing

► SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Solid
Colour: Yellowish
Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

Change in condition:

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** > 150 °C

Flash point: 60 °C

Flammability (solid, gas): Not determined.

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not present an explosion hazard.

Explosion limits:

VIK-COMPOSITE VIK-COMPOSITE

MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

Lower: 0.6 Vol % **Upper:** 7.0 Vol %

Vapour pressure at 20 °C: 1 hPa

Density at 20 °C:about 0.8 g/cm³Relative density:Not determinedVapour density:Not applicableEvaporation rate:Not applicable

Solubility in / Miscibility with water: Insoluble
Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic: Not applicable **Kinematic**: Not applicable

Solvent content:

Organic solvents: 72.0 %

9.2 Other information: No further relevant information available.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5,000 mg/kg (Ratte)
Dermal LD50 >3,000 mg/kg (rab)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

VIK-COMPOSITE VIK-COMPOSITE

MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

STOT-repeated exposure Based on available data, the classification criteria are not met. **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects: Remark: Harmful for fish

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB**: Not applicable.

12.6 Other adverse effects No further relevant information available.

▶ SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recommendation

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: TRANSPORT INFORMATION

14.1 UN-Number ADR, IMDG, IATA

14.2 UN proper shipping name

ADR

IMDG

IATA

UN3077

3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Naphtha (petroleum), hydrotreated heavy) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (Naphtha (petroleum), hydrotreated heavy), MARINE

POLLUTANT

Environmentally hazardous substance, solid, n.o.s. (Naphtha

(petroleum), hydrotreated heavy)

14.3 Transport hazard class(es) ADR, IMDG, IATA



MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

Class 9 Miscellaneous dangerous substances and articles.

Label 9

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards: Product contains environmentally hazardous substances:

Naphtha (petroleum), hydrotreated heavy

Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles.

Danger code (Kemler):90EMS Number:F-A,S-FStowage CategoryA

Stowage Code SW23 When transported in BK3 bulk container, see 7.6.2.12 and

7.7.3.9.

14.7 Transport in bulk according to

Annex II of Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR 5 kg Limited quantities (LQ) Code: E1

Excepted quantities (EQ)Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

Transport category 3
Tunnel restriction code E

IMDG 5 kg Limited quantities (LQ) Code: E1

Excepted quantities (EQ)Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

UN "Model Regulation": UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED

HEAVY), 9, III

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations: Technical instructions (air): Class Share in % NK > 50

Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

VIK-COMPOSITE VIK-COMPOSITE

MATERIAL SAFETY DATA SHEET

SK2TR150-1

Release Agent

► SECTION 16: OTHER INFORMATION

The information contained herein is based on our knowledge at the date above and refer only to product indicated and constitutes no guarantee of particular quality.

User is responsible for determining whether the VIK-Composite GmbH product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a VIK-Composite GmbH product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the VIK-Composite GmbH product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Relevant phrases

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

This sheet cancels and replaces any previous edition.