



TECHNICAL DATA SHEET

SK2PP232-3 Heat set peel ply

► DESCRIPTION

SK2PP232-3 is a polyamide high-tenacity heat set peel ply used to texture the surface of a composite laminate. The clean, textured surface after using the peel ply allows the secondary bonding or painting. SK2PP232-3 peel ply may reduce or eliminate the need for sanding or abrading of the surface of a composite part. The peel ply is made of high-tenacity polyamide fiber.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Material type:	Polyamide 66	Standard
Color:	White	
Surface weight:	105 g/m ² ± 5%	GB/T4669-2008
Density:	(22×20) ±5 % (yarn/cm)	FZ/T 01093-2008
Tensile strength (Warp):	≥1600	ISO13934.1
Tensile strength (Weft):	≥1500	ISO13934.1
Max. use temperature*:	232°C	

► SIZE

Thickness	Width	Length
130 - 200µm	1520mm	100m

Shelf life: unlimited

Storage conditions: it is recommended to store at temperature from -20°C until +30°C in original packing.

► NOTE

Other weights or special sizes available on request.

* Maximum use temperature should be determined in actual process conditions. The maximum use temperature depends on the duration at maximum temperature and is process specific, we recommend testing prior to use.