



TECHNICAL DATA SHEET

SK2AT200-3

High temperature double side coated adhesive tape

► DESCRIPTION

It is an all-purpose double-backed polyester tape with a high tack pressure sensitive adhesive system. SK2AT200-3 is 13µm polyester film coated on both sides with a non-silicone adhesive. It is used in different applications like holding and fixing of release plies, release films and breathers and materials during lay-up, vacuum bagging operations and curing process to avoid process errors and to improve part quality. SK2AT200-3 provides fast, simple and clean application. Its high adhesive system is UV and chemical resistant. High quick stick offers fast and secure bond on different types of surfaces.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Carrier type:	Polyester
Adhesive type:	Acrylic
Color:	White
Total thickness:	100µm
Carrier thickness:	10µm
Combined adhesive thickness:	90µm
Tensile strength:	22.3 n/25.4 mm
Elongation:	<50%
Maximum use temperature:	205°C

► SIZE

Width	Length
25,4mm	33m
50,8mm	33m

Shelf life: 12 months minimum in original packing.

Storage conditions: It is recommended to store at temperature from -20°C until +30°C in the original packing.

► NOTE

Other sizes are available on special order.