



TECHNICAL DATA SHEET

SK2AT205-3

Adhesive Tape

► DESCRIPTION

SK2AT205-3 tape is used for adhesive flash clean-up over or next the bond lines or anywhere extra strength is needed. It can be also used to aid in potting inserts, drilling through SK2AT205-3.

Tape is high temperature and tensile strength polyester film coated with pressure sensitive silicone adhesive. SK2AT205-3 could be used in oven and autoclave, such as to perform in protection in chemical milling or acid bath etching.

There are multi-purpose functions for composite industry, like holding down vacuum bagging materials, thermocouple wires, masking-of and chemical milling protection.

The tape removes easily after the cure.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Carrier type:	Polyester
Adhesive type:	Silicone
Color:	Blue
Total thickness:	170µm
Carrier thickness:	130µm
Adhesive thickness:	40µm
Maximum use temperature	205°C
Elongation on break:	120%

► SIZE

Width	Length	Packaging
25mm	33m	36 rolls/cs
50mm	33m	16 rolls/cs

Shelf life: 12 months minimum in original packing.

Storage conditions: It is recommended to store at temperature from +10°C until +30°C in the original packing.

► NOTE

Other sizes are available on special order.