



TECHNICAL DATA SHEET

SK2AT200-7

Double-sided polyester film adhesive tape

► DESCRIPTION

SK2AT200-7 is polyester film coated with acrylic adhesive on both sides. The product has excellent bonding and very high adhesion and provides reliable sticking effect.

This product is used in various manufacturing processes of parts made of composite materials.



► TECHNICAL DATA

Carrier type:	Polyester
Adhesive type:	Acrylic
Colour of carrier:	Translucent
Colour of liner:	Yellow
Total thickness:	125µm
Carrier thickness:	12µm PET
Adhesive thickness:	56.5µm x 2
Yellow glassine paper liner:	90g
Maximum use temperature:	205°C





TECHNICAL DATA SHEET

SK2AT200-7

Double-sided polyester film adhesive tape

► APPLICATION

- Suitable for kinds of nameplates and film switches mounting and fixing;
- Good filling for rigid-to-rigid substrate bonding;
- For dimensional stability and improved handling with ease of die cutting and laminating;
- Adhesion to plastic and foam, attach gaskets and LED lens on cellular phones and pagers.

► SIZE

Width	Length	Packaging
25mm	50m	48 rolls/cs
50mm	50m	24 rolls/cs

Shelf life: 24 months minimum in original packing.

Storage conditions: it is recommended to store at +22°C, humidity 50%, kept away from wet and heat source.

► NOTE

Maximum use temperature should be determined under your actual process conditions.