VIK-COMPOSITE VIK-COMPOSITE

TECHNICAL DATA SHEET

SK2AT204-2

Economical adhesive tape

DESCRIPTION

AT204-2 tape is a stronger version of AT204-1, used anywhere extra strength is needed. Tape is high temperature and tensile strength polyester film coated with pressure sensitive silicone adhesive. SK2AT204-2 could be used in oven and autoclave for flash breaking application, holding down vacuum bagging materials and thermocouples. This tape is designed to perform in masking applications and chemical milling protection requiring high chemical resistance. The tape removes easily after the cure.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Carrier type:

Adhesive type:

Color


Total thickness:

Carrier thickness:

Adhesive thickness:

Maximum use temperature

Polyester
Silicone
Blue
85µm
50µm
204°C







TECHNICAL DATA SHEET

SK2AT204-2

Economical adhesive tape

► SIZE

Reference for order	Width	Length
SK2AT204-2BL85MC12.566	12,5mm	66m
SK2AT204-2BL85MC2566	25mm	66m
SK2AT204-2BL85MC5066	50mm	66m

Shelf life: 24 months minimum in original packing.

Storage conditions: It is recommended to store at temperature from +10°C until +30°C in the original packing.

▶ NOTE

Other sizes are available on special order.