



TECHNICAL DATA SHEET

SK2ST210-2

Sealant tape with high tack and clean remove

► DESCRIPTION


SK2ST210-2 is an economical multi-purpose sealant tape with high tack. It removes very easily from metal or composite tools without leaving any marks due to its new improved composition. Usable up to 210°C cures in oven or autoclave.

For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.

This product is used in various manufacturing processes of parts made of composite materials.

► TECHNICAL DATA

Material:	Synthetic rubber
Color:	Yellow
Maximum use temperature:	210°C



► SIZE

Thickness	Width	Length	Packing
3mm	12mm	7,5m	40 rolls / case

Shelf life: 24 months minimum with the respect to the storage conditions.

Storage conditions: it is recommended to store at temperatures between +10°C and +30°C stored flat in original packing.



TECHNICAL DATA SHEET

SK2ST210-2

Sealant tape with high tack and clean remove

► **NOTE**

The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, we recommend testing prior to use.

All surfaces should be clean, dry and free from grease and loose materials. Apply directly from the reel onto one surface and press sufficiently along its whole length to achieve good initial adhesion. Remove backing paper and offer other surface to the tape and push firmly to seal across the joint.