



SK2PP190-2

Light polyamide tight woven peel ply

SK2PP190-2 is a light polyamide tight woven peel ply with good performance when used with epoxy, vinyl and polyester resins in the process till 190°C. It has red tracers with high visibility to reduce the risk of peel ply being left on the part. SK2PP190-2 gives a slightly textured surface to the laminate that allows making secondary operations such as bonding or painting. This product is used in various manufacturing processes of parts made of composite materials.

| TECHNICAL DATA | VALUE |
|--------------------------|---------------------------|
| Material type | Nylon (Polyamide) |
| Color | White |
| Stripes | Red |
| Surface weight | 64 g/m ² ± 10% |
| Maximum use temperature* | 190°C |

| SIZE | |
|-----------|---------|
| Thickness | 70 µm |
| Width | 1570 mm |
| Length | 100 m |

STORAGE

Shelf life: unlimited.
Storage conditions: it is recommended to store at temperatures between -20°C and +30°C in original packing

NOTES

Peel plies are treated in order to remove all pollutant products (like silicones for example), which could be found on the laminate. Other weights or special sizes available on request.
* Maximum use temperature should be determined in actual process conditions. The maximum use temperature depends on the duration at maximum temperature and is process specific, we recommend testing prior to use.

Technical values are provided to the best of our knowledge and are based on data considered reliable. Users are responsible for verifying suitability and assume all associated risks.