

# TECHNICAL DATA SHEET

## SK2VV232-5

### Multi cartridge tree

The multi cartridge tree provides a multi-point connection for extra line capacity. A single threaded or QRC inlet can be adapted to either a threaded connection or used a quick disconnect, outlet connectors provide extra capacity (any other configurations or number of outlet connectors are available at special request). Quick disconnect plugs are fitted with high temperature seals and are fully resealable. All parts are manufactured from carbon steel and Manufactured to ISO B.

This product is used in various manufacturing processes of parts made of composite materials.



TECHNICAL DATA	VALUE
Material type	Carbon steel
Material type of O-ring seal	High temperature Viton 232°C
Coupling size	1/4
Treaded size	¼ inch female BSP
Maximum autoclave pressure	10 bar

TREE TYPE	CONNECTION	1 Inlet
SK2VV232-51/3QRCx1QRC	3 x QRC 1/4	QRC 1/4
SK2VV232-51/4QRCx1QRC	4 x QRC 1/4	QRC 1/4
SK2VV232-52/3QRCx1BSP1/4	3 x QRC 1/4	1/4 inch female BSP
SK2VV232-52/3QRCx1BSP1/4	2 x QRC 1/4	1/4 inch female BSP
SK2VV232-52/2QRCx1BSP1/4	8 x QRC 1/4	1/4 inch female BSP

#### STORAGE

It is recommended to store at temperature from +10°C until +30°C in the original packing.

#### NOTES

All end fittings passed vacuum tightness test after assembly. Recommended maintenance interval 1000 hours based on operating temperatures up to 180°C when using with our connections.

Technical values are provided to the best of our knowledge and are based on data considered reliable. Users are responsible for verifying suitability and assume all associated risks.