



SK2AT205-6

All-purpose polyester adhesive tape with non-silicone adhesive

SK2AT205-6 is a strong tear resistant polyester film combined with a high temperature resistant, proprietary blended, rubber adhesive. The strong, comformable, polyester backing allows easy removal with no breaking or slivering. The high temperature, non-silicone adhesive will strip clean leaving only minimum residue. This tape is an excellent choice in applications where silicone contamination is unacceptable.

This product is used in various manufacturing processes of parts made of composite materials.



TECHNICAL DATA	VALUE
Carrier type	Polyester
Adhesive type	High temperature rubber
Color	Green
Elongation at break	100%
Maximum use temperature*	205°C

SIZE	
Total thickness	80 µm
Carrier thickness	30 µm
Adhesive thickness	50 µm
Width	25 mm and 50 mm as standard
Length	66 m

STORAGE

Shelf life: 12 months minimum in original packing.
Storage conditions: It is recommended to store the product in cool dry area in the original packing away from direct sunlight.

NOTES

*Maximum use temperature should be determined in actual process conditions. We recommend to test the product before use in serial production.
These products are not suitable for prolonged outdoor exposure.
Packing: in rolls packed with shrinkable plastic film. Then in paper cartons.

Technical values are provided to the best of our knowledge and are based on data considered reliable. Users are responsible for verifying suitability and assume all associated risks.