



SK2PP220-1

Robust medium weight polyamide peel ply

SK2PP220-1 is an economic peel ply, which is high in quality, yet inexpensive. It is designed to work in resin infusion, autoclave or hand lay-up processes. Using of SK2PP220-1 assists or eliminates the need for sanding or braiding on your composite laminate. This peel ply could be used with epoxy, polyester and vinylester resins in the processes till 232°C.

This product is used in various manufacturing processes of parts made of composite materials.



TECHNICAL DATA	VALUE
Material type	Nylon (Polyamide)
Color	White
Stripes	Red / or without stripes
Surface weight	85 g/m ²
Recommended use temperature	220°C
Maximum use temperature*	232°C
SIZE	
Thickness	130 µm
Width	1520 mm
Length	200 m

STORAGE

Shelf life: unlimited.

Storage conditions: it is recommended to store at temperatures between -20°C and +30°C in original packing

NOTES

Peel plies are treated in order to remove all pollutant products (like silicones for example), which could be found on the laminate. Depending on the customer's process it is possible to supply this peel ply with or without stripes in order to eliminate the print of the tracer on the surface of the laminate during the curing process. Hot knife slitting of the 1 master roll is possible upon request. 1 master roll is a minimum order quantity. Other widths and length of roll available at special order. Maximum width of the roll is 1800mm.

* Maximum use temperature should be determined in actual process conditions. The maximum use temperature depends on the duration at maximum temperature and is process specific, we recommend testing prior to use.