



SK2ST210-2

Sealant tape with high tack and clean remove

SK2ST210-2 is an economical multi-purpose sealant tape with high tack. It removes very easily from metal or composite tools without leaving any marks due to its new improved composition. Usable up to 210°C cures in oven or autoclave. For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.

This product is used in various manufacturing processes of parts made of composite materials.



TECHNICAL DATA	VALUE
Material	Synthetic rubber
Color	Yellow
Maximum use temperature*	210°C

Instructions for application:

The surface should be clean, dry, smooth and dust-free.

- Place the stripe into the surface avoiding air bubbles with release paper on top;
- Remove the easy peel release film;
- Lay the film on top of the strip;
- Apply pressure by hand and/or roller SK3ROL-1 to ensure tight connection;

SIZE

Thickness	3 mm
Width	12 mm
Length	7,5 m
Rolls in Box	40 rolls
MOQ	1 box

STORAGE

Shelf life: 24 months minimum with the respect to the storage conditions.
Storage conditions: it is recommended to store at temperatures between +10°C and +30°C stored flat in original packing.

NOTES

*The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, we recommend testing prior to use.

Technical values are provided to the best of our knowledge and are based on data considered reliable. Users are responsible for verifying suitability and assume all associated risks.