



SK2ST230-3 is multi-purpose sealant tape which can be easily removed from metal or composite tools without leaving any marks due to its new improved composition. The product can be used for curing in oven or autoclave. It demonstrates excellent performance on both composite and metal tools, suitable for oven and autoclave applications.

For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.



TECHNICAL DATA	VALUE
Material	Synthetic polymer butyl based
Color	Green
Maximum use temperature*	230°C

Instructions for application:

The surface should be clean, dry, smooth and dust-free.

- Place the stripe into the surface avoiding air bubbles with release paper on top;
- Remove the easy peel release film;
- Lay the film on top of the strip;
- Apply pressure by hand and/or roller SK3ROL-1 to ensure tight connection;

SIZE

Thickness	3 mm
Width	12 mm
Length	7,5 m
Rolls in Box	40 rolls
MOQ	1 box

STORAGE

Shelf life: 12 months minimum in original packing.
 Storage conditions: it is recommended to store at temperatures between +10°C and +30°C in original packing; if stored at a temperature between +10°C and +30°C the product must be used within 6 months; if stored at a temperature between +10°C and +25°C the product must be used within 12 months. The product is not affected by frost.

NOTES

*Maximum use temperature should be determined in actual process conditions. We recommend to test the product before use in serial production.

Technical values are provided to the best of our knowledge and are based on data considered reliable. Users are responsible for verifying suitability and assume all associated risks.